

Claims

I Claim:

- 5 1. An adapter for a toilet flushing apparatus to
simplify installation of said apparatus comprising a
generally tubular body having a top, a bottom, an
internal surface and an external surface, said top
internal surface having means for affixing to the
10 base of a toilet flushing apparatus said bottom
having at least two descending legs wherein said at
least two legs having a locking means for securing
said apparatus within a toilet.
2. An adapter according to claim 1 wherein said at
15 least two descending legs are semi-flexible.
3. An adapter according to claim 2 having three
descending legs.
4. An adapter according to claim 2 having four
descending legs.
- 20 5. An adapter according to claim 1 wherein said at
least two legs have a upper portion closer to said
generally tubular body bottom and a base distant
from said generally circular body.
6. An adapter according to claim 1 wherein locking
25 means is a snap-clip located at said base of said at
least two legs.
7. A toilet flushing apparatus further comprising an
adapter to simplify installation said adapter
comprising a generally tubular body having a top, a
30 bottom, an internal surface and an external surface,
said top internal surface having threads for
affixing to the base of a toilet flushing apparatus
said bottom having at least two descending legs

- wherein said at least two legs having a locking means for securing said apparatus within a toilet.
8. A toilet flushing apparatus central riser comprising a generally tubular main body, having a top, a bottom, a first outlet port on said top, a second outlet port on said main body near said bottom said second outlet port spaced vertically apart from said first outlet port and an overflow tube extending out from said main body near said top generally parallel with said main body, said first outlet port able to receive a first stopper affixed to said top, said second port able to receive a second stopper affixed to said main body and a means for affixing a stopper activation means to said main body and said bottom having at least two descending legs, said legs having locking means to secure said central riser within a toilet tank.
9. A toilet flushing apparatus central riser according to claim 9 further comprising a seat for affixing a washer on said bottom side of said main body positioned above said at least two legs.
10. A toilet flushing apparatus central riser according to claim 9 wherein said at least two descending legs are semi-flexible.
11. A toilet flushing apparatus central riser according to claim 9 having three descending legs.
12. A toilet flushing apparatus central riser according to claim 9 having four descending legs.
13. A toilet flushing apparatus central riser according to claim 9 wherein said locking means is a snap-clip locking means.